



Features:

- Motor: Capacitor-Run Induction Motor
- Motor Protection: Thermal Protected
- Bearing Type: Two Ball
- Connection: UL 1430 AWG 22, 300mm Wire Leads or Terminal
- Frame Material: Aluminum Alloy
- Impeller Material: Plastic UL94V-0
- Operating Temp:
Two Ball: -10°C~70°C
- Life Expectancy:
Two Ball: 50,000 Hours



Fan-S Division




Model No.	Volt.	Freq.	Current	Power	Rated Speed	Maximum AirFlow		Maximum Static Pressure		Noise Level	Weight
	(VAC)	(Hz)	(A)	(W)	(rpm)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
FKA2-28089NBH** 3F-A	115	50/60	1.70/2.84	185.0/300.0	2800/3200	39.1/41.9	1380/1480	1.30/0.94	33.0/24.0	73.0/75.0	3500
FKA2-28089QBH** 3F-A	230	50/60	0.80/1.29	185.0/290.0	2800/3200	39.1/41.9	1380/1480	1.30/0.94	33.0/24.0	73.0/75.0	3500

** Indicates "W" (Wire Leads) or "T" (Terminal)

Noise is measured at the distance of one (1) meter from the axis of intake.

50Hz



60Hz

