
THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.

| REVISION | | | | | | |
|----------|-------------|------|----------|--|--|--|
| REV. | DESCRIPTION | DATE | APPROVED | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |



CONTROLLED

NOTES:

- 1. CORDAGE: H05VVH2-F, 2x0.75mm 2C, UNSHIELDED, CEE COLOR CODE, TEMP. RATING 70°C, RATING: 250V 6A, JACKET COLOR: BLACK
- 2. PLUG: IEC 884/EN 50 075
- 3. CONNECTOR: ROJ 50mm, STRIP 5mm
- 4. APPROVALS: ITALY
- 5. ROHS COMPLIANT

| Dim range | Tolerance +/- | Qualtek Electronics Corp. PPC DIVISION | | | |
|--------------|------------------|---|-------------------------|-------------------|--|
| (mm) | (mm) | Part Number: 3 | 79002-E01 | RoHS Compliant | |
| 0-1 | 0.15 | Description: POWER CORD | | | |
| 1-6 | 0.20 | POWER CORD | | | |
| 6-18 | 0.30 | | LINUT | | |
| 18-50 | 0.50 | 1 | UNIT: mm | | |
| 50-120 | 0.70 | Drawn / Date | Checked / Date | Approved / Date | |
| 120-250 | 0.90 | R. Nuti | 06-25-07 JJH / 06-25-07 | | |
| 250-500 | 1.20 | 06-25-07 | 00-25-07 | 3311/ 00-23-07 | |